


Combined luminaire for general and emergency lighting Luminaire with targeted light output. Robust trapezoidal luminaire housing for wall mounting made of powder-coated die-cast aluminium. High protection rating for outdoor installation. And optional cable entry at the side. Incl. four cable entries for through-wiring to general and emergency lighting. External supply unit: IP66; Ta: -5...+40 °C


**Technical data**

<b>Rated duration:</b>	1h;1,5h;2h;3h;8h	<b>Effective power:</b>	5,5 W
<b>Battery type:</b>	Ni-MH 4,8 V 1,1 Ah	<b>Inrush current:</b>	11 A / 64 µs
<b>Material:</b>	die-cast aluminum	<b>Protection class:</b>	I
<b>Illuminant:</b>	9 x 0,32W LED-module	<b>Input terminals:</b>	max. 2,5mm <sup>2</sup> single-core
<b>Nominal voltage AC:</b>	230V AC ±10% 50/60 Hz	<b>Temperature ta:</b>	-15...+40 °C
<b>Nominal current AC:</b>	28 mA	<b>Impact resistance:</b>	IK09
<b>Apparent power:</b>	6,5 VA		

**Technical data (General lighting)**

<b>Nominal voltage AC:</b>	230V AC/DC ±10% 50/60 Hz	<b>Light colour:</b>	3000 K
<b>Apparent power:</b>	12,5 VA	<b>Luminous flux:</b>	918 lm
<b>Leistung (Allgemeinlicht):</b>	10,4 W	<b>inrush current:</b>	8 A / 50 µs



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8




Distance to middle of escape route	Distance to middle of escape route					
	1.0m	2.0m	3.0m	4.0m	5.0m	6.0m
<b>1h</b>	65%					
1.0	2.3	5.6	1.9	5.2	0.0	0.0
2.0	3.2	7.8	3.1	7.8	2.5	7.1
3.0	3.7	9.2	3.6	9.3	3.2	8.9
4.0	3.9	10.1	3.9	10.4	3.6	10.1
5.0	3.9	10.7	4.0	11.0	3.7	10.8
<b>3h</b>	30%					
1.0	1.8	4.5	1.1	3.6	0.0	0.0
2.0	2.5	6.2	2.1	5.9	0.9	4.7
3.0	2.7	7.2	2.5	7.0	1.7	6.2
4.0	2.6	7.6	2.4	7.5	1.6	6.9
5.0	2.1	7.5	1.9	7.5	0.6	6.9
<b>8h</b>	15%					
1.0	1.2	4.0	0.0	0.0	0.0	0.0
2.0	1.5	3.4	0.0	0.0	0.0	0.0
3.0	1.1	5.5	0.0	0.0	0.0	0.0

**Articles**

BN/A/V 6201 SV/B LED 1-8/D						
Colors	DB 703	HWF 7015	RAL 7015	RAL 9016	HWF 9016	HWF (special)
Art. no.	104365128	104365330	104364926	104364825	104365229	104365431
	wall mounting	Light colour: 3000 K		Protection category: IP65		

**BN-supply AP SV/B LED - 1-8/DSKII IP66** Art. no. 102024091

required



<b>Name</b>	<b>Accessories</b>	<b>Art. no.</b>
BN-supply AP SV/B LED - 1-8/DSKII IP66	required	102024091
mounting adapter 6201 RAL 7015	optional	104575292