



High quality LED edge lights made of brushed stainless steel. Homogeneous illumination of the frameless, free hanging 20 mm acrylic legend panel by state-of-the-art LED technology.

Technical data

viewing distance:	30 m	Nominal current AC:	27 mA
Rated duration:	1h;1,5h;2h;3h;8h	Apparent power:	6,2 VA
Battery type:	Ni-MH 4,8 V 1,1 Ah	Inrush current:	11 A / 64 µs
Material:	stainless steel	Protection class:	I
Illuminant:	18 x 0,1W LED-module	Input terminals:	max. 2,5mm ² single-core
Nominal voltage AC:	230V AC ±10% 50/60 Hz	Temperature ta:	M: -5...+35 °C, NM: 0...+40 °C

Articles



BNP 1118.2 E SV/B LED 1-8/D		
Colors	stainless steel	RAL 9016
Art. no.	101399655	101399756

recessed box for concrete ceiling inst. Art. no. 100922537

recessed ceiling mounting

Light colour: 6500 K

Protection category: IP20



Name	Accessories	Art. no.
Battery 4,8 V / 1,1 Ah, block	spare part	101428048
EB LED SV/B 1-8/D modul	spare part	101418045
Legend panel 1018 PL / PR 20mm	required	101457350
Legend panel 1018 PL wht 20mm	required	101463717
Legend panel 1018 PLO / PRO 20mm	required	100941836
Legend panel 1018 PLO / wht 20mm	required	100942240
Legend panel 1018 PLU / PRU 20mm	required	100941937
Legend panel 1018 PLU / wht 20mm	required	100942442
Legend panel 1018 PO / wht 20mm	required	100942038
Legend panel 1018 PR wht 20mm	required	101458360
Legend panel 1018 PRO / wht 20mm	required	100942139
Legend panel 1018 PRU / wht 20mm	required	100942341
Legend panel 1018 PU / PU 20mm	required	101457249
Legend panel 1018 PU / wht 20mm	required	101458259
recessed box for concrete ceiling inst.	optional	100922537

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

