



Single sided aluminium profile emergency exit luminaires with additional light output at bottom side. Homogeneous illumination by state-of-the-art LED technology with a luminance of > 500 cd/m<sup>2</sup>.

**Technical data**


<b>viewing distance:</b>	20 m
<b>Rated duration:</b>	1h;1,5h;2h;3h;8h
<b>Battery type:</b>	Ni-MH 4,8 V 1,1 Ah
<b>Material:</b>	aluminium
<b>Illuminant:</b>	1 x 1W LED-module
<b>Nominal voltage AC:</b>	230V AC ±10% 50/60 Hz

<b>Nominal current AC:</b>	26 mA
<b>Apparent power:</b>	5,9 VA
<b>Inrush current:</b>	11 A / 64 µs
<b>Protection class:</b>	I
<b>Input terminals:</b>	max. 2,5mm <sup>2</sup> single-core
<b>Temperature ta:</b>	M: -5...+35 °C, NM: 0...+40 °C

**Articles**

<b>BNP 7186.1 SV/B LED 1-8/D</b>	
Colors	Aluminium
Art. no.	101406022

wall mounting      Light colour: 6500 K      Protection category: IP40



Name	Accessories	Art. no.
Battery 4,8 V / 1,1 Ah, block	spare part	101428048
Cover 7x86 / 7x20 opal		101203837
EB LED SV/B 1-8/D modul	spare part	101418045
LM 7186.1 1/6,5K KB90	spare part	104529321
Legend panel 7x86 / 2420 PL	required	101211113
Legend panel 7x86 / 2420 PL without logo	required	101213133
Legend panel 7x86 / 2420 PLO	required	101217880
Legend panel 7x86 / 2420 PLO without logo	required	101214648
Legend panel 7x86 / 2420 PLU	required	101217678
Legend panel 7x86 / 2420 PLU without logo	required	101214446
Legend panel 7x86 / 2420 PO	required	101214749
Legend panel 7x86 / 2420 PO without logo	required	101214244
Legend panel 7x86 / 2420 PR	required	101211214
Legend panel 7x86 / 2420 PR without logo	required	101213234
Legend panel 7x86 / 2420 PRO	required	101217981
Legend panel 7x86 / 2420 PRO without logo	required	101214547
Legend panel 7x86 / 2420 PRU	required	101217779
Legend panel 7x86 / 2420 PRU without logo	required	101214345
Legend panel 7x86 / 2420 PU	required	101211012
Legend panel 7x86 / 2420 PU without logo	required	101213032
Protection grid 7186 / 7188 / 7118 / 7181	optional	101441485
special legend panel 7x86 / 2420	required	101223540

**Info:** When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

