


Versatile LED safety luminaire ideal for escape route or staircase illumination. UV resistant, heat filament tested polycarbonate housing for wall mounting with optional side cable entry.

Technical data

Rated duration:	1h;1,5h;2h;3h;8h
Luminous flux:	1h = 65% ; 3h = 30% ; 8h = 15%
Battery type:	Ni-MH 4,8 V 1,1 Ah
Material:	polycarbonate
Illuminant:	3 x 1W LED-module
Nominal voltage AC:	230V AC ±10% 50/60 Hz

Nominal current AC:	33 mA
Apparent power:	7,5 VA
Inrush current:	11 A / 64 µs
Protection class:	II
Input terminals:	max. 2,5mm ² single-core
Temperature ta:	M: -5...+35 °C, NM: 0...+40 °C




Wall mounting: Minimum illumination 1.0lx
 (m) (m) (m) te), Maintenance factor 0.8

1h	65%		
1.0	1.8	4.3	
2.0	2.4	6.1	
3.0	2.5	7.0	
4.0	2.3	7.4	
5.0	1.5	7.1	
3h	30%		
1.0	1.4	3.7	
2.0	1.7	4.8	
3.0	1.4	5.1	
8h	15%		
1.0	1.0	3.0	
2.0	1.0	3.6	

Articles

BN 2004.1 SV/B LED 1-8/D		
Colors	Polycarbonat	RAL (special)
Art. no.	101403089	104659764

wall mounting Light colour: 6500 K Protection category: IP40



Name	Accessories	Art. no.
Battery 4,8 V / 1,1 Ah, blocklong	spare part	101428250
EB LED SV/B 1-8/D modul	spare part	101418045
LM SN/BN 2004.1 3/6,5K KB200 LED Modul	spare part	104428681