


Versatile LED safety luminaire ideal for escape route or staircase illumination. UV resistant, heat filament tested polycarbonate housing for wall mounting with optional side cable entry.

**Technical data**

<b>Rated duration:</b>	1h;1,5h;2h;3h;8h
<b>Luminous flux:</b>	1h = 65% ; 3h = 30% ; 8h = 15%
<b>Battery type:</b>	Ni-MH 4,8 V 1,1 Ah
<b>Material:</b>	polycarbonate
<b>Illuminant:</b>	3 x 1W LED-module
<b>Nominal voltage AC:</b>	230V AC ±10% 50/60 Hz

<b>Nominal current AC:</b>	33 mA
<b>Apparent power:</b>	7,5 VA
<b>Inrush current:</b>	11 A / 64 µs
<b>Protection class:</b>	II
<b>Input terminals:</b>	max. 2,5mm <sup>2</sup> single-core
<b>Temperature ta:</b>	M: -5...+35 °C, NM: 0...+40 °C



Wall mounting: Minimum illumination 1.0lx  
 (m) (m) (m) te), Maintenance factor 0.8

<b>1h</b>	65%		
1.0	1.8	4.3	
2.0	2.4	6.1	
3.0	2.5	7.0	
4.0	2.3	7.4	
5.0	1.5	7.1	
<b>3h</b>	30%		
1.0	1.4	3.7	
2.0	1.7	4.8	
3.0	1.4	5.1	
<b>8h</b>	15%		
1.0	1.0	3.0	
2.0	1.0	3.6	

**Articles**

<b>BN 2004.1 SV/B LED 1-8/D</b>	
Colors	Polycarbonat
Art. no.	101403089

Name	Accessories	Art. no.
Battery 4,8 V / 1,1 Ah, blocklong	spare part	101428250
EB LED SV/B 1-8/D modul	spare part	101418045
LM SN/BN 2004.1 3/6,5K KB200	spare part	104428681

wall mounting      Light colour: 6500 K      Protection category: IP40

