


Functional LED downlight with a flat design and asymmetric light distribution, ideal for escape route illumination. UV resistant, heat filament tested polycarbonate housing with optional side cable entry.

Technical data

Rated duration:	1h;1,5h;2h;3h;8h	Nominal current AC:	33 mA
Luminous flux:	1h = 45% ; 3h = 25% ; 8h = 9%	Apparent power:	7,5 VA
Battery type:	Ni-MH 4,8 V 1,1 Ah	Inrush current:	11 A / 64 µs
Material:	polycarbonate	Protection class:	II
Illuminant:	2 x 1W LED-module	Input terminals:	max. 2,5mm ² single-core
Nominal voltage AC:	230V AC ±10% 50/60 Hz	Temperature ta:	M: -5...+35 °C, NM: 0...+40 °C



Minimum illumination 1.0lx (area illumination),
Maintenance factor 0.8

	2.5	3.0	3.5	4.0	5.0
1h ☺	45%				
2.5	1.3	3.4	13.8	5.6	
3.0	1.3	3.5	15.0	6.2	
4.0	0.9	3.7	17.1	6.7	
5.0	0.2	2.2	11.9	6.1	
3h ☺	25%				
2.5	0.9	2.7	11.8	4.7	
3.0	0.7	2.7	12.8	5.0	
3.5	0.1	2.6	13.5	0.2	
8h ☺	9%				

Articles

BN 2040.1 B SV/B LED 1-8/D			Name	Accessories	Art. no.
Colors	Polycarbonat	RAL (special)	Battery 4,8 V / 1,1 Ah, blocklong	spare part	101428250
Art. no.	101402887	101402988	EB LED SV/B 1-8/D modul	spare part	101418045
			assembly unit BN / SN 2040.1-BLED	spare part	101174333

ceiling mounting

Light colour: 6500 K

 Protection category:
IP40
