




Universal LED downlight ideal for escape route illumination. UV resistant, heat filament tested polycarbonate housing with optional side cable entry and comfortable installation space.

Technical data

Rated duration:	1h;1,5h;2h;3h;8h	Apparent power:	8,5 VA
Battery type:	Ni-MH 4,8 V 1,1 Ah	Inrush current:	11 A / 64 µs
Illuminant:	4 x 1W LED-module	Protection class:	II
Nominal voltage AC:	230V AC ±10% 50/60 Hz	Input terminals:	max. 2,5mm ² single-core
Nominal current AC:	37 mA	Temperature ta:	M: -5...+35 °C, NM: 0...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

	1h	1.5h	2h	3h	8h
1h	50%				
2.5	3.2	7.6	8.1	3.2	
3.0	3.6	8.3	8.7	3.3	
4.0	3.5	9.7	9.4	3.4	
5.0	3.2	9.8	9.6	3.1	
6.0	2.5	9.7	9.4	2.4	
3h		25%			
2.5	2.4	6.6	6.5	2.3	
3.0	2.4	7.0	6.7	2.3	
4.0	1.9	7.0	6.8	1.9	
8h		10%			
2.5	1.3	4.4	4.3	1.2	

Articles

BN 2130 SV/B LED 1-8/D	
Colors	Polycarbonat
Art. no.	101403291




BN 2130 SV/B LED 1-8/D	
Colors	Polycarbonat
Art. no.	101403594

Light colour: 6500 K

Protection category: IP40

Light colour: 6500 K

Protection category: IP65


Frame for recessed ceilingmounting 2130 Art. no. 101428856


BN 2130 Polycarbonate luminaires

Self-contained LED luminaires with bus-connection to BNS-MTB

Name	Accessories	Art. no.
Battery 4,8 V / 1,1 Ah, sideby side	spare part	101428149
Cover SN 2130, clear	spare part	100612844
Cover-sticker for 2130 / 2718, white	required	101199894
EB LED SV/B 1-8/D modul	spare part	101418045
Frame for recessed ceilingmounting 2130	optional	101428856
LED replacement kit SN 2130 /SNP 2230	spare part	101943360
Piktogrammscheibe 2130 PL /PR 5mm		101429260
Piktogrammscheibe 2130 PL /PR 5mm		101453815
Piktogrammscheibe 2130 PU /PU 5mm		101429159
Piktogrammscheibe 2130 PU /PU 5mm		101453714

Info:

