




Safety- / Exit luminaire for EX-Zone 1, 21, 2, 22 according to ATEX-classification Group II category 2 G D. Luminaire for ceiling / wall mounting, made of high-quality die-cast aluminium.

Delivery incl. 2 x cable gland made of polyamide. Ex-marking of the gland: II 2 G Ex e IIC Gb, II 2 D Ex tb IIIC Db IP68.

Technical data

viewing distance:	30 m	Nominal current DC:	200 mA
Material:	die-cast aluminum	Protection class:	III
Illuminant:	4 x 1W LED-module	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±20 %	Temperature ta:	-20...+55 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

(m)	2.5	4.7	11.6	7.4	2.9
2.5	4.7	11.6	7.4	2.9	
3.0	4.8	12.6	8.0	2.9	
4.0	4.9	13.7	8.3	3.2	
5.0	4.9	14.0	8.8	3.6	
6.0	4.7	14.2	9.7	3.9	
7.0	4.2	14.0	10.0	2.3	
8.0	3.3	13.6	-	-	

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

(m)	2.5	2.3	5.9	7.2	2.5
2.5	2.3	5.9	7.2	2.5	
3.0	2.5	6.5	7.8	2.5	
4.0	3.0	7.2	8.5	3.0	
5.0	3.2	8.1	9.4	3.3	
6.0	3.3	9.0	10.5	3.3	
7.0	3.3	8.0	11.2	2.3	
8.0	2.0	7.0	11.2	2.0	

Articles

EX 7000 LED 24V	
Colors	-
Art. no.	101335189
wall or ceiling mounting	Light colour: 6500 K
	Protection category: IP66

Name	Accessories	Art. no.
picto attachment incl. picto set EX 7000	required	101467353

