

230V**EX 7102 EX - Luminaires****J/SV**

For connection to JOKER-central battery systems




Ex-safety- /exit-luminaire for zone 1, 2, 21, 22. Made of high-quality glass fiber reinforced polyester resin for wall or ceiling mounting.

Technical data

viewing distance:	30 m
Material:	polyester, polycarbonate
illuminant:	LED-module
Luminous flux:	510 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	28 mA

Nominal current DC:	25 mA
Apparent power:	6,5 VA
Effective power:	6,0 W
Inrush current:	35 A / 95 µs
Protection class:	I
Temperature ta:	-30...+60 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Distance (m)	1	2	3	4	5
2.0	2.8	9.4	11.1	4.4	
3.0	4.3	10.1	12.7	4.9	
4.0	4.7	12.0	13.7	5.2	
5.0	4.8	12.8	14.5	5.3	
6.0	4.8	13.3	14.9	5.2	
7.0	4.6	13.6	15.1	5.0	
8.0	4.1	13.6	15.0	4.5	
9.0	3.4	13.4	14.6	3.7	
10.0	2.0	12.9	14.0	2.2	

Articles

EX 7102 LED J/SV	
Colors	-
Art. no.	101284366

Name	Accessories	Art. no.
Picto-set EX 710x PU, PL, PR	required	101464424

wall or ceiling mounting Light colour: 6500 K Protection category: IP66

