





Dynamic single-sided Straight-Line emergency exit sign luminaire made of high quality, powder-coated aluminium. Ideal to display the safe escape route depending on the smoke situation inside a building.

Technical data

viewing distance:	20 m	Apparent power:	5,6 VA
Material:	aluminium powder-coated	Effective power:	5,3 W
Illuminant:	LED-module	Inrush current:	6 A / 22 µs
Nominal voltage AC:	230V ±10% 50/60 Hz	Protection class:	I
Nominal voltage DC:	176 - 264 V	Input terminals:	2.5mm ² feed through wiring
Nominal current AC:	24 mA	Temperature ta:	-15...+40 °C
Nominal current DC:	23 mA		

Articles

FL 1520 PM CLDD 230V			FL 1520 WE CLDD 230V		
Colors	RAL 9016	RAL (special)	Colors	RAL 9016	RAL (special)
Art. no.	101828071	101828172	Art. no.	101828475	101828576
wall mounting		Protection category: IP40	recessed wall mounting		Protection category: IP40



Name	Accessories	Art. no.
AU FL 1520 CLDD 230V PL, RAL 9016	required	101836357
AU FL 1520 CLDD 230V PR, RAL 9016	required	101836559

Info: When ordering a module luminaire, the required pictogram with the corresponding arrow direction and other equipment must be indicated.

PL: PR:

