



Dynamic single-sided Straight-Line emergency exit sign luminaire made of high quality, powder-coated aluminium. Ideal to display the safe escape route depending on the smoke situation inside a building.

## Technical data

<b>viewing distance:</b>	30 m
<b>Material:</b>	aluminium powder-coated
<b>Illuminant:</b>	LED-module
<b>Nominal voltage AC:</b>	230V ±10% 50/60 Hz
<b>Nominal voltage DC:</b>	176 - 264 V
<b>Nominal current AC:</b>	26 mA
<b>Nominal current DC:</b>	26 mA


<b>Apparent power:</b>	5,9 VA
<b>Effective power:</b>	5,6 W
<b>Inrush current:</b>	6 A / 22 µs
<b>Protection class:</b>	I
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C

## Articles

FL 1530 PM CLDD 230V		
Colors	RAL 9016	RAL (special)
Art. no.	101827263	101827364

wall mounting


Protection category:  
IP40



FL 1530 WE CLDD 230V		
Colors	RAL 9016	RAL (special)
Art. no.	101827667	101827768

recessed wall mounting

Protection category:  
IP40



Name	Accessories	Art. no.
AU FL 1530 CLDD 230V PL, RAL 9016	required	101835347
BG FL 1530 CLDD 230V PR, RAL 9016	required	101835145

**Info:** When ordering a module luminaire, the required pictogram with the corresponding arrow direction and other equipment must be indicated.

PL: PR:

