



Dynamic single-sided Straight-Line emergency exit sign luminaire made of high quality, powder-coated aluminium. Ideal to display the safe escape route depending on the smoke situation inside a building.

Technical data

viewing distance:	30 m
Material:	aluminium powder-coated
Illuminant:	LED-module
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	26 mA
Nominal current DC:	26 mA

Apparent power:	5,9 VA
Effective power:	5,6 W
Inrush current:	6 A / 22 µs
Protection class:	I
Input terminals:	2.5mm² feed through wiring
Temperature ta:	-15...+40 °C


Articles

FL 1530 PM FLDD 230V

Colors	RAL 9016	RAL (special)
Art. no.	101386016	101386117

parallel wall mounting

Protection category:
IP40




FL 1530 WE FLDD 230V

Colors	RAL 9016	RAL (special)
Art. no.	101386824	101386925

recessed wall mounting

Protection category:
IP40



Name	Accessories	Art. no.
AU FL 1530 FLDD 230V PL, RAL 9016	required	101483016
AU FL 1530 FLDD 230V PR, RAL 9016	required	101482814
AU FL 1530 WA FLDD 230V PL, RAL 9016	required	101483420
AU FL 1530 WA FLDD 230V PR, RAL 9016	required	101483218

Info: When ordering a module luminaire, the required pictogram with the corresponding arrow direction and other equipment must be indicated.

PL:

PR:

