



Dynamic single-sided Straight-Line emergency exit sign luminaire made of high quality, powder-coated aluminium. Ideal to display the safe escape route depending on the smoke situation inside a building.

Technical data


viewing distance:	30 m	Nominal current DC:	230 mA
Material:	aluminium powder-coated	Protection class:	III
Illuminant:	LED-module	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±25 %	Temperature ta:	-15...+40 °C

Articles

FL 1530 PM ILDD 24V		
Colors	RAL 9016	RAL (special)
Art. no.	100864539	100864640

parallel wall mounting


Protection category:
IP40



FL 1530 WE ILDD 24V		
Colors	RAL 9016	RAL (special)
Art. no.	100864943	100865044

recessed wall mounting

Protection category:
IP40



Name	Accessories	Art. no.
AU FL 1530 ILDD 24V PL, RAL 9016	required	101485945
AU FL 1530 WA ILDD 24V PL, RAL9016	required	101486349
AU FL 1530 WA ILDD 24V PR, RAL9016	required	101486551
BG FL 1530 ILDD 24V PR, RAL 9016	required	101486147

Info: When ordering a module luminaire, the required pictogram with the corresponding arrow direction and other equipment must be indicated.

PL:

PR:

