



Low level recessed wall installation luminaire for dynamic indication of the safe escape route depending on the smoke spreading during a fire. Luminaire with powder-coated metal cover for installation in double wall box for concrete, cavity wall or in-wall.

Technical data

| | | | |
|----------------------------|---------------------------|--------------------------|--|
| Material: | sheet steel powder-coated | Apparent power: | 3,7 VA |
| Illuminant: | LED-module | Effective power: | 4,1 W |
| Nominal voltage AC: | 230V ±10% 50/60 Hz | Inrush current: | 6 A / 22 µs |
| Nominal voltage DC: | 176 - 264 V | Protection class: | I |
| Nominal current AC: | 16 mA | Input terminals: | 2.5mm ² feed through wiring |
| Nominal current DC: | 14 mA | Temperature ta: | -15...+40 °C |

Articles

| FL 6110 CLDD 230V | | | Name | Accessories | Art. no. |
|-------------------|-----------|---------------|-------------------------------------|-------------|----------|
| Colors | RAL 9016 | RAL (special) | 32 WL-SMTW 1500MCD/20MA GRÜNKB 60MM | spare part | 092405 |
| Art. no. | 101829586 | 101829687 | CLDD 230/8-CC-125-300-C | | 860050 |

recessed wall mounting

 Protection category:
 IP40
