



Dynamic single-sided emergency exit sign luminaire made of high quality aluminium profile. Ideal to display the safe escape route depending on the smoke situation inside a building.

## Technical data

<b>viewing distance:</b>	35 m
<b>Material:</b>	aluminium
<b>illuminant:</b>	LED-module
<b>Nominal voltage AC:</b>	230V ±10% 50/60 Hz
<b>Nominal voltage DC:</b>	176 - 264 V
<b>Nominal current AC:</b>	24 mA
<b>Nominal current DC:</b>	22 mA

<b>Apparent power:</b>	5,6 VA
<b>Effective power:</b>	5,2 W
<b>Inrush current:</b>	6 A / 22 µs
<b>Protection class:</b>	I
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C

## Articles

FL 7188 CLDD 230V		
Colors	Aluminium	RAL (special)
Art. no.	101950737	101826556

Name	Accessories	Art. no.
BG FL 7X88 CLDD 230V PL	required	101970238
BG FL 7X88 CLDD 230V PR	required	101970339

wall mounting

Protection category:  
IP40

**Info:** When ordering a module luminaire, the required pictogram with the corresponding arrow direction and other equipment must be indicated.

