



Dynamic single-sided emergency exit sign luminaire made of high quality aluminium profile. Ideal to display the safe escape route depending on the smoke situation inside a building.

### Technical data


<b>viewing distance:</b>	35 m	<b>Apparent power:</b>	5,6 VA
<b>Material:</b>	aluminium	<b>Effective power:</b>	5,2 W
<b>Illuminant:</b>	LED-module	<b>Inrush current:</b>	6 A / 22 $\mu$ s
<b>Nominal voltage AC:</b>	230V $\pm$ 10% 50/60 Hz	<b>Protection class:</b>	I
<b>Nominal voltage DC:</b>	176 - 264 V	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Nominal current AC:</b>	24 mA	<b>Temperature ta:</b>	-15...+40 °C
<b>Nominal current DC:</b>	22 mA		

### Articles

FL 7188 FLDD 230V		Name	Accessories	Art. no.
Colors	Aluminium	BG FL 7X88 FLDD 230V PL	required	101486955
Art. no.	101384093	BG FL 7X88 FLDD 230V PR	required	101487056

wall mounting

Protection category:  
IP40



**Info:** When ordering a module luminaire, the required pictogram with the corresponding arrow direction and other equipment must be indicated.

