



Dynamic double-sided emergency exit sign luminaire made of high quality aluminium profile. Ideal to display the safe escape route depending on the smoke situation inside a building.
 For single-sided use, the current consumption is reduced by 50%.

Technical data


viewing distance:	35 m
Material:	aluminium
illuminant:	LED-module
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	49 mA
Nominal current DC:	44 mA

Apparent power:	11,2 VA
Effective power:	10,4 W
Inrush current:	6 A / 22 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C

Articles



FL 7288 K CLDD 230V		
Colors	Aluminium	RAL (special)
Art. no.	101951141	101826960

chain mounting

 Protection category:
 IP40



FL 7288 P CLDD 230V		
Colors	Aluminium	RAL (special)
Art. no.	101951040	101826859

pendulum mounting

 Protection category:
 IP40



FL 7288 D CLDD 230V		
Colors	Aluminium	RAL (special)
Art. no.	101950838	101826657

ceiling mounting

 Protection category:
 IP40


FL 7288 WA CLDD 230V		
Colors	Aluminium	RAL (special)
Art. no.	101950939	101826758

wall bracket mounting

 Protection category:
 IP40




FL 7288 Aluminium luminaires

for connection to CP D.E.R. 230V

Name	Accessories	Art. no.
AU blind plate FL 7X88	required	101444822
BG FL 7X88 CLDD 230V PL	required	101970238
BG FL 7X88 CLDD 230V PR	required	101970339
Pendulum set SN-luminaire BUS0,5 m wh	required	101439061
Pendulum set SN-luminaire BUS1,0 wh	required	101439263
Pendulum set SN-luminaire BUS2,0 m wh	required	101439465

Info: When ordering a module luminaire, the required pictogram with the corresponding arrow direction and other equipment must be indicated.

PL:

PR:



Info: For luminaires with pendulum mounting, select the desired pendulum (length and colour of baldachin).