



Dynamic double-sided emergency exit sign luminaire made of high quality aluminium profile. Ideal to display the safe escape route depending on the smoke situation inside a building.

For single-sided use, the current consumption is reduced by 50%.

### Technical data

<b>viewing distance:</b>	35 m	<b>Apparent power:</b>	11,2 VA
<b>Material:</b>	aluminium	<b>Effective power:</b>	10,4 W
<b>Illuminant:</b>	LED-module	<b>Inrush current:</b>	6 A / 22 $\mu$ s
<b>Nominal voltage AC:</b>	230V $\pm$ 10% 50/60 Hz	<b>Protection class:</b>	I
<b>Nominal voltage DC:</b>	176 - 264 V	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Nominal current AC:</b>	49 mA	<b>Temperature ta:</b>	-15...+40 °C
<b>Nominal current DC:</b>	44 mA		

### Articles


#### FL 7288 D FLDD 230V

Colors Aluminium

Art. no. 101384295

ceiling mounting

Protection category:  
IP40




#### FL 7288 K FLDD 230V

Colors Aluminium

Art. no. 100864236

chain mounting

Protection category:  
IP40




#### FL 7288 P FLDD 230V

Colors Aluminium

Art. no. 100864135

pendulum mounting

Protection category:  
IP40




#### FL 7288 WA FLDD 230V

Colors Aluminium

Art. no. 101384396

wall bracket mounting

Protection category:  
IP40



Name	Accessories	Art. no.
AU FL 7X88 FLDD 230V PL	required	101486955
AU FL 7X88 FLDD 230V PR	required	101487056
AU blind plate FL 7X88	required	101444822
Pendulum set SN-luminaire 0,5m gr	required	101439566
Pendulum set SN-luminaire 0,5m wh	required	101438960
Pendulum set SN-luminaire 1,0m gr	required	101439768
Pendulum set SN-luminaire 1,0m wh	required	101439162
Pendulum set SN-luminaire 2,0m gr	required	101439970
Pendulum set SN-luminaire 2,0m wh	required	101439364

**Info:** When ordering a module luminaire, the required pictogram with the corresponding arrow direction and other equipment must be indicated.

PL:

PR:



**Info:** For luminaires with pendulum mounting, select the desired pendulum (length and colour of baldachin).