



Dynamic double-sided emergency exit sign luminaire made of high quality aluminium profile. Ideal to display the safe escape route depending on the smoke situation inside a building.

For single-sided use, the current consumption is reduced by 50%.


Technical data

viewing distance:	35 m	Nominal current DC:	460 mA
Material:	aluminium	Protection class:	III
illuminant:	LED-module	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±25 %	Temperature ta:	-15...+40 °C

Articles


FL 7288 D ILDD 24V

Colors	Aluminium	RAL (special)
Art. no.	101392177	101392278
ceiling mounting		Protection category: IP40




FL 7288 K ILDD 24V

Colors	Aluminium	RAL (special)
Art. no.	101392783	101392884
chain mounting		Protection category: IP40




FL 7288 P ILDD 24V

Colors	Aluminium	RAL (special)
Art. no.	101392581	101392682
pendulum mounting		Protection category: IP40



FL 7288 WA ILDD 24V

Colors	Aluminium	RAL (special)
Art. no.	101392379	101392480
wall bracket mounting		Protection category: IP40



FL 7288 Aluminium luminaires

For connection to CLS FUSION, CPUSB...24V or 24V change-over device

Name	Accessories	Art. no.
AU FL 7X88 ILDD 24V PL	required	101487359
AU FL 7X88 ILDD 24V PR	required	101487460
AU blind plate FL 7X88	required	101444822
Pendulum set SN-luminaire 0,5m gr	required	101439566
Pendulum set SN-luminaire 0,5m wh	required	101438960
Pendulum set SN-luminaire 1,0m gr	required	101439768
Pendulum set SN-luminaire 1,0m wh	required	101439162
Pendulum set SN-luminaire 2,0m gr	required	101439970
Pendulum set SN-luminaire 2,0m wh	required	101439364

Info: When ordering a module luminaire, the required pictogram with the corresponding arrow direction and other equipment must be indicated.

PL:

PR:



Info: For luminaires with pendulum mounting, select the desired pendulum (length and colour of baldachin).