



Dynamic double-sided emergency exit sign luminaire made of high quality aluminium profile. Ideal to display the safe escape route depending on the smoke situation inside a building.

For single-sided use, the current consumption is reduced by 50%.

Technical data


viewing distance:	35 m	Nominal current DC:	460 mA
Material:	aluminium	Protection class:	III
Illuminant:	LED-module	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±25 %	Temperature ta:	-15...+40 °C

Articles

FL 7288 D ILDD 24V		
Colors	Aluminium	RAL (special)
Art. no.	101392177	101392278

ceiling mounting


Protection category:
IP40



FL 7288 K ILDD 24V		
Colors	Aluminium	RAL (special)
Art. no.	101392783	101392884

chain mounting


Protection category:
IP40



FL 7288 P ILDD 24V		
Colors	Aluminium	RAL (special)
Art. no.	101392581	101392682

pendulum mounting


Protection category:
IP40



FL 7288 WA ILDD 24V		
Colors	Aluminium	RAL (special)
Art. no.	101392379	101392480

wall bracket mounting

Protection category:
IP40



Name	Accessories	Art. no.
BG FL 7X88 Blindplatte	required	101444822
BG FL 7X88 ILDD 24V PL	required	101487359
BG FL 7X88 ILDD 24V PR	required	101487460
Pendulum set SN-luminaire 0,5m gr	required	101439566
Pendulum set SN-luminaire 0,5m wh	required	101438960
Pendulum set SN-luminaire 1,0m gr	required	101439768
Pendulum set SN-luminaire 1,0m wh	required	101439162
Pendulum set SN-luminaire 2,0m gr	required	101439970
Pendulum set SN-luminaire 2,0m wh	required	101439364

Info: When ordering a module luminaire, the required pictogram with the corresponding arrow direction and other equipment must be indicated.

PL:

PR:



Info: For luminaires with pendulum mounting, select the desired pendulum (length and colour of baldachin).