

230V**FL 808** Stainless steel luminaire

For connection to FUSION central battery- or emergency power (NEA) systems



Dynamic single-sided emergency exit luminaire made of robust stainless steel with high protection category. Ideal to display the safe escape route depending on the smoke situation inside a building.

Technical data

| | |
|----------------------------|--------------------|
| viewing distance: | 30 m |
| Material: | stainless steel |
| Illuminant: | LED-module |
| Nominal voltage AC: | 230V ±10% 50/60 Hz |
| Nominal voltage DC: | 176 - 264 V |
| Nominal current AC: | 24 mA |
| Nominal current DC: | 22 mA |


| | |
|--------------------------|--|
| Apparent power: | 5,6 VA |
| Effective power: | 5,2 W |
| Inrush current: | 6 A / 22 µs |
| Protection class: | I |
| Input terminals: | 2.5mm ² feed through wiring |
| Temperature ta: | -15...+40 °C |

Articles

| FL 808 FLDD 230V | |
|-------------------------|-----------------|
| Colors | stainless steel |
| Art. no. | 101383790 |

| Name | Accessories | Art. no. |
|------------------------|--------------------|-----------------|
| AU FL 8X8 FLDD 230V PL | required | 101486753 |
| AU FL 8X8 FLDD 230V PR | required | 101486854 |

wall mounting

Protection category:
IP65

Info: When ordering a module luminaire, the required pictogram with the corresponding arrow direction and other equipment must be indicated.

