



Dynamic double-sided emergency exit luminaire made of robust stainless steel with high protection category. Ideal to display the safe escape route depending on the smoke situation inside a building. For single-sided use, the current consumption is reduced by 50%.

Technical data


viewing distance:	30 m	Nominal current DC:	460 mA
Material:	stainless steel	Protection class:	III
Illuminant:	LED-module	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±25 %	Temperature ta:	-15...+40 °C

Articles

FL 828 K ILDD 24V

Colors	stainless steel	RAL 7015	RAL 9016	RAL (special)
Art. no.	101391167	101391369	101391268	101391470


chain mounting

Protection category:
IP65

FL 828 WA ILDD 24V

Colors	stainless steel	RAL 7015	RAL 9016	RAL (special)
Art. no.	101391571	101391773	101391672	101391874

wall bracket mounting

Protection category:
IP65

Name	Accessories	Art. no.
AU FL 8X8 ILDD 24V PR	required	101487258
AU blind plate FL 8X8	required	101444923
BG FL 8X8 ILDD 24V PL	required	101487157

Info: When ordering a module luminaire, the required pictogram with the corresponding arrow direction and other equipment must be indicated.

PL:

PR:

