



LED outdoor luminaire for safety and/or general lighting. Robust die-cast aluminium housing with weatherproof powder coating, high IP65 protection and impact resistance IK10.



Technical data


Material:	die-cast aluminum
Illuminant:	replaceable 10 x 0,2W + 18 x 0,3W LED-module
Luminous flux:	209 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	19 mA
Nominal current DC:	16 mA

Apparent power:	4,4 VA
Effective power:	3,9 W
Inrush current:	6 A / 22 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10

Technical data (General lighting)

Nominal voltage AC:	230V AC/DC ±10% 50/60 Hz
Apparent power:	10,4 VA
Effective power:	7,2 W

Light colour:	3000 K, 4000 K
Luminous flux:	601 lm
inrush current:	8 A / 50 µs



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Distance to middle of escape route (m)	1.0m	2.0m	3.0m
2.5	3.2	8.3	
3.0	3.3	8.7	
4.0	3.2	9.2	
5.0	2.9	9.3	
6.0	2.1	9.0	


Wall mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Distance to middle of escape route (m)	1.0m		2.0m	
	2.0	5.8	6.6	2.2
2.5	1.8	5.7	6.7	2.1
3.0	1.2	5.3	6.5	1.8

Articles


SN/A 6200 FLD 230V round		
Colors	RAL 7024	RAL 9003
Art. no.	101382881	101382780

wall or ceiling mounting Light colour: 3000 K Protection category: IP65



SN/A 6200 FLD 230V round		
Colors	RAL 7024	RAL 9003
Art. no.	101382679	101382578

wall or ceiling mounting Light colour: 4000 K Protection category: IP65



Name	Accessories	Art. no.
Cover 6200 RD	spare part	104776669
FLD 230/8 – CC – 320 – C	spare part	100903238

Info:

