



LED outdoor luminaire for safety and/or general lighting. Robust die-cast aluminium housing with weatherproof powder coating, high IP65 protection and impact resistance IK10.



### Technical data


<b>Material:</b>	die-cast aluminum
<b>Illuminant:</b>	replaceable 10 x 0,2W + 18 x 0,3W LED-module
<b>Luminous flux:</b>	209 lm
<b>Nominal voltage AC:</b>	230V ±10% 50/60 Hz
<b>Nominal voltage DC:</b>	176 - 264 V
<b>Nominal current AC:</b>	22 mA
<b>Nominal current DC:</b>	17 mA

<b>Apparent power:</b>	5,1 VA
<b>Effective power:</b>	4,0 W
<b>Inrush current:</b>	6 A / 98 µs
<b>Protection class:</b>	I
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C
<b>Impact resistance:</b>	IK10

### Technical data (General lighting)

<b>Nominal voltage AC:</b>	230V AC/DC ±10% 50/60 Hz
<b>Apparent power:</b>	10,4 VA
<b>Effective power:</b>	7,2 W

<b>Light colour:</b>	3000 K, 4000 K
<b>Luminous flux:</b>	601 lm
<b>inrush current:</b>	8 A / 50 µs



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Distance to middle of escape route (m)	1.0m	2.0m	3.0m
2.5	3.2	8.3	
3.0	3.3	8.7	
4.0	3.2	9.2	
5.0	2.9	9.3	
6.0	2.1	9.0	


Wall mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Distance to middle of escape route (m)	1.0m		2.0m	
	2.0	2.5	5.8	6.6
2.0	2.0	5.7	6.6	2.2
2.5	1.8	5.7	6.7	2.1
3.0	1.2	5.3	6.5	1.8

### Articles


SN/A 6200 LED J/SV round		
Colors	RAL 7024	RAL 9003
Art. no.	101279013	101278912

wall or ceiling mounting    Light colour: 3000 K    Protection category: IP65



SN/A 6200 LED J/SV round		
Colors	RAL 7024	RAL 9003
Art. no.	101278811	101278710

wall or ceiling mounting    Light colour: 4000 K    Protection category: IP65



Name	Accessories	Art. no.
Cover 6200 RD	spare part	104776669
J-ET 5.1 SV-max. 24V DC320mA const.	spare part	101422893

Info:

