

230V

SN/A 6200 RD Wall, floor and stair luminaires

J/SV

For connection to JOKER-central battery systems



LED outdoor luminaire for safety and/or general lighting. Robust die-cast aluminium housing with weatherproof powder coating, high IP65 protection and impact resistance IK10.

**Technical data**


Material:	die-cast aluminum
Illuminant:	10 x 0,2W + 18 x 0,3W LED-module
Luminous flux:	209 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	22 mA
Nominal current DC:	17 mA

Apparent power:	5,1 VA
Effective power:	4,0 W
Inrush current:	6 A / 98 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10

Technical data (General lighting)

Nominal voltage AC:	230V AC/DC ±10% 50/60 Hz
Apparent power:	10,4 VA
Leistung (Allgemeinlicht):	7,2 W

Light colour:	3000 K, 4000 K
Luminous flux:	601 lm
inrush current:	8 A / 50 µs



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Distance to middle of escape route [m]	3000 K	4000 K
2.5	3.2	8.5
3.0	3.3	8.9
4.0	3.3	9.4
5.0	2.9	9.5
6.0	2.1	9.2


Wall mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Distance to middle of escape route [m]	Distance to middle of escape route			
	1.0m		2.0m	
2.0	2.3	6.3	6.7	2.4
2.5	2.2	6.4	6.9	2.3
3.0	1.8	6.1	6.7	2.0

Articles


SN/A 6200 LED J/SV round		
Colors	RAL 7024	RAL 9003
Art. no.	101279013	101278912

wall or ceiling mounting Light colour: 3000 K Protection category: IP65



SN/A 6200 LED J/SV round		
Colors	RAL 7024	RAL 9003
Art. no.	101278811	101278710

wall or ceiling mounting Light colour: 4000 K Protection category: IP65



Name	Accessories	Art. no.
J-ET 5.1 SV-max. 24V DC320mA const.	Ersatzteil	101422893