



LED outdoor luminaire for safety and/or general lighting. Robust die-cast aluminium housing with weatherproof powder coating, high IP65 protection and impact resistance IK10.



Technical data


| | |
|----------------------------|----------------------|
| Material: | die-cast aluminum |
| Illuminant: | 10 x 0,2W LED-module |
| Luminous flux: | 194 lm |
| Nominal voltage DC: | 24 V ±25 % |
| Nominal current DC: | 115 mA |

| | |
|---------------------------|--|
| Protection class: | I |
| Input terminals: | 2.5mm ² feed through wiring |
| Temperature ta: | -15...+40 °C |
| Impact resistance: | IK10 |

Technical data (General lighting)

| | |
|----------------------------|--------------------------|
| Nominal voltage AC: | 230V AC/DC ±10% 50/60 Hz |
| Apparent power: | 10,4 VA |
| Light colour: | 3000 K, 4000 K |

| | |
|------------------------|-------------|
| Luminous flux: | 549 lm |
| inrush current: | 8 A / 50 μs |



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

| Distance to middle of escape route (m) | 1.0m | 2.0m |
|--|------|------|
| 2.5 | 3.2 | 8.3 |
| 3.0 | 3.3 | 8.7 |
| 4.0 | 3.2 | 9.2 |
| 5.0 | 2.8 | 9.3 |
| 6.0 | 1.8 | 8.9 |

Wall mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8


| Distance to middle of escape route (m) | 1.0m | | 2.0m | |
|--|------|------|------|------|
| | 1.0m | 2.0m | 1.0m | 2.0m |
| 2.0 | 2.1 | 6.0 | 6.5 | 2.3 |
| 2.5 | 2.2 | 6.1 | 6.7 | 2.3 |
| 3.0 | 1.4 | 6.0 | 6.8 | 2.0 |

Articles

SN/A 6200 LED 24V square

| | | |
|-----------------|-----------|-----------|
| Colors | RAL 7024 | RAL 9003 |
| Art. no. | 101350347 | 101350246 |

wall or ceiling mounting Light colour: 3000 K Protection category: IP65



SN/A 6200 LED 24V square

| | | |
|-----------------|-----------|-----------|
| Colors | RAL 7024 | RAL 9003 |
| Art. no. | 101350145 | 101350044 |

wall or ceiling mounting Light colour: 4000 K Protection category: IP65

