

230V SN/A 6308 Wall, floor and stair luminaires

FLD For connection to FUSION central battery- or emergency power (NEA) systems



Combined bollard safety luminaire optimised for the illumination of escape routes in outdoor areas. Luminaires made of high-quality, powder-coated aluminium with a high protection category.

Technical data


Material:	aluminium powder-coated
Illuminant:	1 x 3,5W LED-module
Luminous flux:	340 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	25 mA
Nominal current DC:	25 mA

Apparent power:	5,8 VA
Effective power:	5,5 W
Inrush current:	6 A / 22 µs
Protection class:	II
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C

Technical data (General lighting)

Nominal voltage AC:	230V AC/DC ±10% 50/60 Hz
Apparent power:	7,6 VA
Light colour:	3000 K, 4000 K

Luminous flux:	654 lm
inrush current:	8 A / 50 µs




Wall mounting: Minimum illumination 1.0lx
Maintenance factor 0.8

Distance to middle of escape route		1.0m
1.0	3.5	9.2

Articles


SN/A 6308 FLD 230V		
Colors	RAL 7015	RAL (special)
Art. no.	101397130	101397231

floor installation Light colour: 3000 K Protection category: IP54



SN/A 6308 FLD 230V		
Colors	RAL 7015	RAL (special)
Art. no.	101397332	101397433


floor installation Light colour: 4000 K Protection category: IP54



Wall, floor and stair luminaires

ground element bollard console

Art. no. 101080565



Name	Accessories	Art. no.
FLD 230/4 - CC - 320 - L	Ersatzteil	101965083
LM 6308 2/3K ALB KB80	Ersatzteil	104576104
LM 6308 2/4K ALB KB80	Ersatzteil	104576205
ground element bollard console	optional	101080565