




Combined bollard safety luminaire optimised for the illumination of escape routes in outdoor areas. Luminaires made of high-quality, powder-coated aluminium with a high protection category.

### Technical data

<b>Material:</b>	aluminium powder-coated	<b>Nominal current DC:</b>	185 mA
<b>Illuminant:</b>	1 x 3,5W LED-module   LED-module	<b>Protection class:</b>	II
<b>Luminous flux:</b>	340 lm	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Nominal voltage DC:</b>	24 V ±25 %	<b>Temperature ta:</b>	-15...+40 °C

### Technical data (General lighting)

<b>Nominal voltage AC:</b>	230V AC/DC ±10% 50/60 Hz	<b>Luminous flux:</b>	654 lm
<b>Apparent power:</b>	7,6 VA	<b>inrush current:</b>	8 A / 50 µs
<b>Light colour:</b>	3000 K, 4000 K		





Wall mounting: Minimum illumination 1.0lx  
Maintenance factor 0.8

Distance to middle of escape route		1.0m
1.0	3.5	9.2

### Articles

SN/A 6308 LED 24V			SN/A 6308 LED 24V		
Colors	RAL 7015	RAL (special)	Colors	RAL 7015	RAL (special)
Art. no.	100835843	100835944	Art. no.	101356310	101356411
floor installation	Light colour: 3000 K	Protection category: IP54	floor installation	Light colour: 4000 K	Protection category: IP54



**ground element bollard console**

Art. no. 101080565

optional

**Name**

ground element bollard console

**Accessories**

optional

**Art. no.**

101080565

