

230V**SN/A 6308 Wall, floor and stair luminaires****J/SV**

For connection to JOKER-central battery systems




Combined bollard safety luminaire optimised for the illumination of escape routes in outdoor areas. Luminaires made of high-quality, powder-coated aluminium with a high protection category.

Technical data

Material:	aluminium powder-coated	Apparent power:	7,6 VA
Illuminant:	1 x 3,5W LED-module	Effective power:	5,7 W
Luminous flux:	340 lm	Inrush current:	8 A / 50 µs
Nominal voltage AC:	230V ±10% 50/60 Hz	Protection class:	II
Nominal voltage DC:	176 - 264 V	Input terminals:	2.5mm ² feed through wiring
Nominal current AC:	33 mA	Temperature ta:	-15...+40 °C
Nominal current DC:	25 mA		

Technical data (General lighting)

Nominal voltage AC:	230V AC/DC ±10% 50/60 Hz	Luminous flux:	654 lm
Apparent power:	7,6 VA	inrush current:	8 A / 50 µs
Light colour:	3000 K, 4000 K		



Wall mounting: Minimum illumination 1.0lx
Maintenance factor 0.8


Distance to middle of escape route		1.0m
1.0	3.5	9.2

Articles

SN/A 6308 LED J/SV		
Colors	RAL 7015	RAL (special)
Art. no.	101281033	101281134

floor installation


Light colour: 3000 K

Protection category:
IP54

SN/A 6308 LED J/SV		
Colors	RAL 7015	RAL (special)
Art. no.	101281235	101281336

floor installation


Light colour: 4000 K

Protection category:
IP54

Wall, floor and stair luminaires

ground element bollard console

Art. no. 101080565



Name	Accessories	Art. no.
J - ET 9 / 24 SV -max.24VDC,320mAconst	Ersatzteil	101420267
LM 6308 2/3K ALB KB80	Ersatzteil	104576104
LM 6308 2/4K ALB KB80	Ersatzteil	104576205
ground element bollard console	optional	101080565