



LED exit sign luminaire with frameless, freely suspended pictogram screen. Homogeneous pictogram illumination using modern light guide technology. LED carrier for Trilux trunking system E-Line PRO 078...13 LV with snap locks that can be applied tool-free.


Technical data

viewing distance:	20 m
Material:	sheet steel powder-coated
Illuminant:	12 x 0,1W LED-module
Nominal voltage DC:	24 V $\pm$ 25 %
Nominal current DC:	70 mA

Effective power:	1,7 W
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C

Articles

SNP 1020 LED 24V			
Colors	RAL 9005	RAL 9006	RAL 9016
Art. no.	104723220	104723119	104723018
Trilux E-Line PRO 078...13 LV Light colour: 6500 K Protection category: IP20			



Name	Accessories	Art. no.
Blind cover SNP 1020, white	required	101856060
Legend panel SNP 1020, PL	required	101856262
Legend panel SNP 1020, PLO	required	101856666
Legend panel SNP 1020, PLU	required	101856565
Legend panel SNP 1020, PO	required	101856464
Legend panel SNP 1020, PR	required	101856363
Legend panel SNP 1020, PRO	required	101856868
Legend panel SNP 1020, PRU	required	101856767
Legend panel SNP 1020, PU	required	101856161
Legend panel SNP 1020, customdesign	required	101856969

Info:

PO:	PR:	PU:	PL:	PRO:	PRU:	PLU:	PLO: