



LED escape sign panel light with frameless, freely suspended pictogram panel. Homogeneous pictogram illumination thanks to modern light guide technology. LED device carrier for XAL MOVE IT PRO with locking function of the circuit selector switch.


Technical data

viewing distance:	20 m	Apparent power:	4,0 VA
Illuminant:	12 x 0,1W LED-module	Effective power:	3,2 W
Nominal voltage AC:	230V ±10% 50/60 Hz	Inrush current:	6 A / 98 µs
Nominal voltage DC:	176 - 264 V	Protection class:	I
Nominal current AC:	17 mA	Input terminals:	2.5mm ² feed through wiring
Nominal current DC:	14 mA	Temperature ta:	-15...+40 °C

Articles

SNP 1020 MOVE IT PRO LED J/SV		
Colors	RAL 9005	RAL 9016
Art. no.	104906409	104980975

zum Einbau in XAL Lichtband-Light colour: 6500 K Protection category: IP20



Name	Accessories	Art. no.
Blind cover SNP 1020, white	required	101856060
J-ET 5.1 SV-max. 24V DC320mA const.	spare part	101422893
LM 200x12 12/6,5K PADS LED Modul	spare part	104617126
Legend panel SNP 1020, PL	required	101856262
Legend panel SNP 1020, PLO	required	101856666
Legend panel SNP 1020, PLU	required	101856565
Legend panel SNP 1020, PO	required	101856464
Legend panel SNP 1020, PR	required	101856363
Legend panel SNP 1020, PRO	required	101856868
Legend panel SNP 1020, PRU	required	101856767
Legend panel SNP 1020, PU	required	101856161
Legend panel SNP 1020, customdesign	required	101856969

Info:

