SNP 1023.1 Edge lights

For connection to JOKER-central battery systems

INOTEC Sicherheitstechnik GmbH



Functional edge lights made of high quality aluminium profile. Homogeneous illumination of the frameless, free hanging acrylic pictograph by state-of-the-art LED technology.

Technical data

viewing distance:	50 m
Material:	aluminium
Illuminant:	replaceable 12 x 1W LED-module
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	94 mA

Nominal current DC:	85 mA
Apparent power:	21,6 VA
Protection class:	I
Input terminals:	2.5mm² feed through wiring
Temperature ta:	-15...+40 °C


Articles

SNP 1023.1 D LED J/SV

Colors	Aluminium
Art. no.	101261835

ceiling mounting | Light colour: 6500 K | Protection category: IP20






SNP 1023.1 E LED J/SV

Colors	RAL 9016	RAL (special)
Art. no.	101262138	101262239

recessed ceiling mounting | Light colour: 6500 K | Protection category: IP20






SNP 1023.1 P LED J/SV

Colors	Aluminium
Art. no.	101261936

pendulum mounting | Light colour: 6500 K | Protection category: IP20






SNP 1023.1 PM LED J/SV

Colors	Aluminium	RAL (special)
Art. no.	101262340	101262441

parallel wall mounting | Light colour: 6500 K | Protection category: IP20





SNP 1023.1 Edge lights

For connection to JOKER-central battery systems

Name	Accessories	Art. no.
		undefined
	required	undefined
J-ET 9/24 SVmax.24VDC,320mAconst	spare part	101420267
LM 1023.1 12/6,5K KB300 LED Modul	spare part	101941845
Legend panel 1023 PL / PR 20mm	required	101463818
Legend panel 1023 PL / wht 20mm	required	101464020
Legend panel 1023 PR / wht 20mm ISO 7010	required	101464121
Legend panel 1023 PU / PU 20mm	required	101464222
Legend panel 1023 PU / wht 20mm	required	101463919

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

PO: PR: PU: PL: PRO: PRU: PLU: PLO:

