



LED exit sign luminaire with frameless, freely suspended pictogram screen. Homogeneous pictogram illumination using modern light guide technology. LED carrier for Trilux trunking system E-Line PRO 078...13 LV with snap locks that can be applied tool-free.

Technical data


viewing distance:	30 m
Material:	sheet steel powder-coated
Illuminant:	replaceable 18 x 0,1W LED-module
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	19 mA
Nominal current DC:	18 mA

Apparent power:	4,3 VA
Effective power:	3,9 W
Inrush current:	6 A / 22 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C

Articles

SNP 1030 FLD 230V			
Colors	RAL 9005	RAL 9006	RAL 9016
Art. no.	104724129	104724028	104723927

Trilux E-Line PRO 078...13 LV Light colour: 6500 K Protection category: IP20



Name	Accessories	Art. no.
Blind cover SNP 1030, white	required	101857070
Legend panel SNP 1030, PL	required	101857272
Legend panel SNP 1030, PLO	required	101857676
Legend panel SNP 1030, PLU	required	101857575
Legend panel SNP 1030, PO	required	101857474
Legend panel SNP 1030, PR	required	101857373
Legend panel SNP 1030, PRO	required	101857878
Legend panel SNP 1030, PRU	required	101857777
Legend panel SNP 1030, PU	required	101857171
Legend panel SNP 1030, customdesign	required	101857979

Info:

