



LED exit sign luminaire with frameless, freely suspended pictogram screen. Homogeneous pictogram illumination using modern light guide technology. LED carrier for Trilux trunking system E-Line PRO 078...13 LV with snap locks that can be applied tool-free.


Technical data

viewing distance:	30 m	Apparent power:	5,2 VA
Material:	sheet steel powder-coated	Effective power:	4,2 W
Illuminant:	replaceable 18 x 0,1W LED-module	Inrush current:	6 A / 98 µs
Nominal voltage AC:	230V ±10% 50/60 Hz	Protection class:	I
Nominal voltage DC:	176 - 264 V	Input terminals:	2.5mm ² feed through wiring
Nominal current AC:	23 mA	Temperature ta:	-15...+40 °C
Nominal current DC:	18 mA		

Articles

SNP 1030 LED J/SV			
Colors	RAL 9005	RAL 9006	RAL 9016
Art. no.	104722917	104722816	104722715

Trilux E-Line PRO 078...13 LV Light colour: 6500 K Protection category: IP20



Name	Accessories	Art. no.
Blind cover SNP 1030, white	required	101857070
Legend panel SNP 1030, PL	required	101857272
Legend panel SNP 1030, PLO	required	101857676
Legend panel SNP 1030, PLU	required	101857575
Legend panel SNP 1030, PO	required	101857474
Legend panel SNP 1030, PR	required	101857373
Legend panel SNP 1030, PRO	required	101857878
Legend panel SNP 1030, PRU	required	101857777
Legend panel SNP 1030, PU	required	101857171
Legend panel SNP 1030, customdesign	101857979	101857979

Info:

