



LED escape sign panel light with frameless, freely suspended pictogram panel. Homogeneous pictogram illumination thanks to modern light guide technology. LED device carrier for XAL MOVE IT PRO with locking function of the circuit selector switch.


Technical data

viewing distance:	30 m	Effective power:	2,4 W
Illuminant:	replaceable 18 x 0,1W LED-module	Protection class:	III
Nominal voltage DC:	24 V $\pm$ 25 %	Input terminals:	2.5mm ² feed through wiring
Nominal current DC:	100 mA	Temperature ta:	-15...+40 °C

Articles

SNP 1030 MOVE IT PRO LED 24V		
Colors	RAL 9005	RAL 9016
Art. no.	104906813	104981278

zum Einbau in XAL Lichtband-Light colour: 6500 K Protection category: IP20



Name	Accessories	Art. no.
Blind cover SNP 1030, white	required	101857070
ILD 24/4-CC-320-L Mini	spare part	104757370
LM 300x12 18/6,5K PADS LED Modul	spare part	104617328
Legend panel SNP 1030, PL	required	101857272
Legend panel SNP 1030, PLO	required	101857676
Legend panel SNP 1030, PLU	required	101857575
Legend panel SNP 1030, PO	required	101857474
Legend panel SNP 1030, PR	required	101857373
Legend panel SNP 1030, PRO	required	101857878
Legend panel SNP 1030, PRU	required	101857777
Legend panel SNP 1030, PU	required	101857171
Legend panel SNP 1030, customdesign	required	101857979

Info:

PO:	PR:	PU:	PL:	PRO:	PRU:	PLU:	PLO: