

230V

SNP 1118.2 E Edge lights

J/SV

For connection to JOKER-central battery systems



High quality LED edge lights made of brushed stainless steel. Homogeneous illumination of the frameless, free hanging 20 mm acrylic legend panel by state-of-the-art LED technology.

Technical data

viewing distance:	30 m	Apparent power:	6,2 VA
Material:	stainless steel brushed	Effective power:	5,2 W
illuminant:	18 x 0,1W LED-module	Inrush current:	8 A / 50 µs
Nominal voltage AC:	230V ±10% 50/60 Hz	Protection class:	I
Nominal voltage DC:	176 - 264 V	Input terminals:	2.5mm ² feed through wiring
Nominal current AC:	27 mA	Temperature ta:	-15...+40 °C
Nominal current DC:	22 mA		

Articles**SNP 1118.2 E LED J/SV**


Colors stainless steel

Art. no. 101242334


recessed ceiling mounting

Light colour: 6500 K

Protection category: IP20

**recessed box for concrete ceiling inst.**

Art. no. 100922537



Name	Accessories	Art. no.
J - ET 9 / 24 SV -max.24VDC,320mAconst	Ersatzteil	101420267
LM 325x21,5 18/6,5K BU	Ersatzteil	101945481
Legend panel 1018 PL / PR 20mm	required	101457350
Legend panel 1018 PL wht 20mm	required	101463717
Legend panel 1018 PLO / PRO 20mm	required	100941836
Legend panel 1018 PLO / wht 20mm	required	100942240
Legend panel 1018 PLU / PRU 20mm	required	100941937
Legend panel 1018 PLU / wht 20mm	required	100942442
Legend panel 1018 PO / wht 20mm	required	100942038
Legend panel 1018 PR wht 20mm	required	101458360
Legend panel 1018 PRO / wht 20mm	required	100942139
Legend panel 1018 PRU / wht 20mm	required	100942341
Legend panel 1018 PU / PU 20mm	required	101457249
Legend panel 1018 PU / wht 20mm	required	101458259
recessed box for concrete ceiling inst.	optional	100922537

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

