

230V

SNP 1118.2 E Edge lights

NE/SV

For connection to INOTEC-NEA-monitoring systems



High quality LED edge lights made of brushed stainless steel. Homogeneous illumination of the frameless, free hanging 20 mm acrylic legend panel by state-of-the-art LED technology.


Technical data

viewing distance:	30 m	Effective power:	4,6 W
Material:	stainless steel brushed	Inrush current:	8 A / 50 μ s
Illuminant:	18 x 0,1W LED-module	Protection class:	I
Nominal voltage AC:	230V AC \pm 10% 50/60 Hz	Input terminals:	2.5mm ² feed through wiring
Nominal current AC:	23 mA	Temperature ta:	-15...+40 °C
Apparent power:	5,3 VA		


Articles

SNP 1118.2 E LED NE/SV	
Colors	stainless steel
Art. no.	101242536

recessed ceiling mounting Light colour: 6500 K Protection category: IP20



recessed box for concrete ceiling inst. Art. no. 100922537



Name	Accessories	Art. no.
LM 325x21,5 18/6,5K BU	Ersatzteil	101945481
Legend panel 1018 PL / PR 20mm	required	101457350
Legend panel 1018 PL wht 20mm	required	101463717
Legend panel 1018 PLO / PRO 20mm	required	100941836
Legend panel 1018 PLO / wht 20mm	required	100942240
Legend panel 1018 PLU / PRU 20mm	required	100941937
Legend panel 1018 PLU / wht 20mm	required	100942442
Legend panel 1018 PO / wht 20mm	required	100942038
Legend panel 1018 PR wht 20mm	required	101458360
Legend panel 1018 PRO / wht 20mm	required	100942139
Legend panel 1018 PRU / wht 20mm	required	100942341
Legend panel 1018 PU / PU 20mm	required	101457249
Legend panel 1018 PU / wht 20mm	required	101458259
NE - ET 9 / 24 SV -max.24VDC,320mAconst	Ersatzteil	101420570
recessed box for concrete ceiling inst.	optional	100922537

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

