




Discrete LED edge lights composed of high-quality anodised aluminium profile without any visible screws. Homogeneous illumination of the free hanging frameless 20 mm acrylic pictograph by state-of-the-art LED technology. Discreet housing thanks to latest 24V technology.

### Technical data


<b>viewing distance:</b>	16 m	<b>Nominal current DC:</b>	45 mA
<b>Material:</b>	aluminium	<b>Protection class:</b>	III
<b>Illuminant:</b>	6 x 0,1W LED-module	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Nominal voltage DC:</b>	24 V ±20 %	<b>Temperature ta:</b>	-15...+40 °C

### Articles


SNP 1214.1 LED 24V	
Colors	Aluminium
Art. no.	102065521
wall or ceiling mounting	Protection category: IP40



SNP 1214.1 S LED 24V	
Colors	Aluminium
Art. no.	102065622
cable suspension mounting	Protection category: IP40



### recessed ceiling set SNP1214.1 RAL 9016 Art. no. 102068046



Name	Accessories	Art. no.
	required	102433616
	required	102433717
	required	102433818
	required	102433919
	required	102434020
	required	102434121
Legend panel 1214 PL / PR 20mm	required	101488369
Legend panel 1214 PL / wht 20mm	required	101488066
Legend panel 1214 PO / PO 20mm	required	101488571
Legend panel 1214 PO / wht 20mm	required	101488268
Legend panel 1214 PR / wht 20mm	required	101487965
Legend panel 1214 PU / PU 20mm	required	101488470
Legend panel 1214 PU / wht 20mm	required	101488167
Legend panel 1216, 20 mm custom design	optional	102162117
Seilset 3m, SNP 101x,10x0,121x,15x0,72xx	optional	102384005
Seilset 5m, SNP 101x,10x0,121x,15x0,72xx	optional	102384106
recessed ceiling set SNP1214.1 RAL 9016	optional	102068046

**Info:** When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

