




Discrete LED edge lights composed of high-quality anodised aluminium profile without any visible screws. Homogeneous illumination of the free hanging frameless 20 mm acrylic pictograph by state-of-the-art LED technology. Discreet housing thanks to latest 24V technology.

Technical data


viewing distance:	22 m	Nominal current DC:	75 mA
Material:	aluminium	Protection class:	III
Illuminant:	12 x 0,1W LED-module	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±20 %	Temperature ta:	-15...+40 °C

Articles

SNP 1216.1 LED 24V	
Colors	Aluminium
Art. no.	102065723
wall or ceiling mounting	Protection category: IP40




SNP 1216.1S LED 24V	
Colors	Aluminium
Art. no.	102065824
cable suspension mounting	Protection category: IP40



Deckeneinbaukit für SNP 1216.1RAL 9016 Art. no. 102068147

optional



Name	Accessories	Art. no.
Legend panel 1216 PL / PR 20mm	required	101489278
Legend panel 1216 PL / wht 20mm	required	101488975
Legend panel 1216 PO / PO 20mm	required	101489480
Legend panel 1216 PO / wht 20mm	required	101489177
Legend panel 1216 PR / wht 20mm	required	101488874
Legend panel 1216 PU / PU 20mm	required	101489379
Legend panel 1216 PU / wht 20mm	required	101489076
Legend panel 1216 VKF 20mm custom design	required	101489682
recessed ceiling frame SNP 1216.1 RAL 9016	optional	102068147

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

