


Versatile LED safety luminaire ideal for illumination of areas to be highlighted especially according to DIN EN 1838. Luminaire with separately switchable, backlit pictograph. UV resistant, heat filament tested polycarbonate housing for wall mounting with optional side cable entry.



Technical data

viewing distance:	18 m	Nominal current DC:	250 mA
Material:	polycarbonate	Protection class:	III
Illuminant:	3 x 1W + 2 x 1W LED-module	Input terminals:	2.5mm ² feed through wiring
Luminous flux:	210 lm	Temperature ta:	-15...+40 °C
Nominal voltage DC:	24 V ±25 %		




Wall mounting: Minimum illumination 1.0lx

Distance to middle of escape route	Distance to middle of escape route					
	1.0m		2.0m		3.0m	
1.0	2.2	5.4	2.3	5.7	1.8	5.2
2.0	2.8	7.0	2.8	7.2	2.3	6.8
2.5	3.0	7.4	3.0	7.8	2.6	7.4
3.0	3.1	8.0	3.1	8.4	2.7	8.1
3.5	3.2	8.5	3.2	8.7	2.8	8.5
4.0	3.1	8.7	3.1	9.1	2.8	8.8
4.5	3.0	9.0	3.0	9.3	2.7	9.0
5.0	2.8	9.0	2.8	9.3	2.5	9.1
5.5	2.6	9.0	2.6	9.3	2.0	9.1
6.0	2.2	8.8	2.1	9.2	1.5	8.9

Articles


SNP 2004.1 LED 24V

Colors	Polycarbonat	RAL (special)
Art. no.	102052585	102053292
wall mounting	Light colour: 6500 K	Protection category: IP40




SNP 2004.1 LED 24V

Colors	Polycarbonat	RAL (special)
Art. no.	102052686	102053393
wall mounting	Light colour: 6500 K	Protection category: IP40




SNP 2004.1 LED 24V

Colors	Polycarbonat	RAL (special)
Art. no.	102052484	102053191
wall mounting	Light colour: 6500 K	Protection category: IP40




SNP 2004.1 LED 24V

Colors	Polycarbonat	RAL (special)
Art. no.	102052181	102052888
wall mounting	Light colour: 6500 K	Protection category: IP40



SNP 2004.1 LED 24V

Colors	Polycarbonat	RAL (special)
Art. no.	102052282	102052989
wall mounting	Light colour: 6500 K	Protection category: IP40

**SNP 2004.1 LED 24V**

Colors	Polycarbonat	RAL (special)
Art. no.	102052383	102053090
wall mounting	Light colour: 6500 K	Protection category: IP40

