



Single sided LED exit luminaire made of UV resistant, heat filament tested polycarbonate housing with optional side cable entry and comfortable installation space. Homogeneous illumination by state-of-the-art LED technology.

Technical data



viewing distance:	30 m
Material:	polycarbonate
illuminant:	replaceable 4 x 1W LED-module
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	27 mA
Nominal current DC:	28 mA

Apparent power:	6,3 VA
Effective power:	6,0 W
Inrush current:	6 A / 22 µs
Protection class:	II
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK05


Articles

SNP 2130 FLD 230V	
Colors	Polycarbonat
Art. no.	100855243
wall mounting	Light colour: 6500 K Protection category: IP40

SNP 2130 FLD 230V	
Colors	Polycarbonat
Art. no.	100855344
wall mounting	Light colour: 6500 K Protection category: IP65



Frame for recessed ceilingmounting 2130 Art. no. 101428856



Name	Accessories	Art. no.
	optional	undefined
Cover 2130 PL	required	101452195
Cover 2130 PLO	required	100932439
Cover 2130 PLU	required	100932641
Cover 2130 PO	required	101453512
Cover 2130 PR	required	101452296
Cover 2130 PRO	required	100932540
Cover 2130 PRU	required	100932742
Cover 2130 PU	required	100932035
Cover 2130, special design	required	101474326
Cover SNP 2130 SETPU/PL/PR		102381678
FLD 230/8 – CC – 320 – C	spare part	100903238
Frame for recessed ceilingmounting 2130	optional	101428856

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

