



Single sided LED exit luminaire made of UV resistant, heat filament tested polycarbonate housing with optional side cable entry and comfortable installation space. Homogeneous illumination by state-of-the-art LED technology.





Technical data


viewing distance:	30 m	Effective power:	5,1 W
Material:	polycarbonate	Protection class:	III
Illuminant:	replaceable 4 x 1W LED-module	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±25 %	Temperature ta:	-15...+40 °C
Nominal current DC:	210 mA	Impact resistance:	IK05

Articles

SNP 2130 LED 24V		SNP 2130 LED 24V	
Colors	Polycarbonat	Colors	Polycarbonat RAL (special)
Art. no.	101353579	Art. no.	101353680 102208492
wall mounting	Light colour: 6500 K Protection category: IP40	wall mounting	Light colour: 6500 K Protection category: IP65



Frame for recessed ceilingmounting 2130 Art. no. 101428856



Name	Accessories	Art. no.
	optional	undefined
Cover 2130 PL	required	101452195
Cover 2130 PLO	required	100932439
Cover 2130 PLU	required	100932641
Cover 2130 PO	required	101453512
Cover 2130 PR	required	101452296
Cover 2130 PRO	required	100932540
Cover 2130 PRU	required	100932742
Cover 2130 PU	required	100932035
Cover 2130, special design	required	101474326
Cover SNP 2130 SETPU/PL/PR		102381678
Frame for recessed ceilingmounting 2130	optional	101428856
ILD 24/4-CC-320-C	spare part	101425321
LMC SNP/BNP 2130 LED Modul und Umrüstsatz	spare part	101943259

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

