



Single sided LED exit luminaire made of UV resistant, heat filament tested polycarbonate housing with optional side cable entry and comfortable installation space. Homogeneous illumination by state-of-the-art LED technology.



**Technical data**



<b>viewing distance:</b>	30 m
<b>Material:</b>	polycarbonate
<b>Illuminant:</b>	replaceable 4 x 1W LED-module
<b>Nominal voltage AC:</b>	230V AC ±10% 50/60 Hz
<b>Nominal current AC:</b>	36 mA
<b>Apparent power:</b>	8,3 VA

<b>Effective power:</b>	7,4 W
<b>Inrush current:</b>	8 A / 50 µs
<b>Protection class:</b>	II
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C
<b>Impact resistance:</b>	IK05


**Articles**

SNP 2130 LED NE/SV	
Colors	Polycarbonat
Art. no.	101271737
wall mounting	Light colour: 6500 K Protection category: IP40

SNP 2130 LED NE/SV	
Colors	Polycarbonat
Art. no.	101272040
wall mounting	Light colour: 6500 K Protection category: IP65



**Frame for recessed ceilingmounting 2130** Art. no. 101428856



Name	Accessories	Art. no.
	required	undefined
	optional	undefined
Cover 2130 PL	required	101452195
Cover 2130 PLO	required	100932439
Cover 2130 PLU	required	100932641
Cover 2130 PO	required	101453512
Cover 2130 PR	required	101452296
Cover 2130 PRO	required	100932540
Cover 2130 PRU	required	100932742
Cover 2130 PU	required	100932035
Cover 2130, special design	required	101474326
Cover SNP 2130 SETPU/PL/PR		102381678
Frame for recessed ceilingmounting 2130	optional	101428856
LMC SNP/BNP 2130 LED Modul und Umrüstsatz	spare part	101943259
NE-ET 9/24 SVmax.24VDC,320mAconst	spare part	101420570

**Info:** When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

