



Single-sided exit sign luminaire made of high-quality aluminum profile. Especially flat design and an efficient and homogeneous illumination of the pictogram, using modern light guide technology. For easy and flexible installation, the cable entry is possible from the rear and from the side.


Technical data

viewing distance:	35 m
Material:	aluminium
Illuminant:	18 x 0,1W LED-module
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	25 mA
Nominal current DC:	16 mA

Apparent power:	5,7 VA
Effective power:	3,5 W
Inrush current:	6 A / 34 µs
Protection class:	I
Input terminals:	2.5mm² feed through wiring
Temperature ta:	-15...+40 °C

Articles

SNP 7135 FLD 230V		
Colors	Aluminium	RAL (special)
Art. no.	101961750	104674619
wall mounting	Light colour: 6500 K	Protection category: IP40



Name	Accessories	Art. no.
FLD 230/4 - CC - 320 - L	spare part	101965083
Legend panel 7x35 PL	required	101948212
Legend panel 7x35 PLO	required	101947707
Legend panel 7x35 PLU	required	101947909
Legend panel 7x35 PO	required	101948010
Legend panel 7x35 PR	required	101948111
Legend panel 7x35 PRO	required	101947606
Legend panel 7x35 PRU	required	101947808
Legend panel 7x35 PU	required	101948313
Legend panel 7x35 custom design		101871016
Spare part - LED unit SNP 7135	spare part	101969531

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

