




Single-sided exit sign luminaire made of high-quality aluminum profile. Especially flat design and an efficient and homogeneous illumination of the pictogram, using modern light guide technology. For easy and flexible installation, the cable entry is possible from the rear and from the side.

Technical data

viewing distance:	35 m	Apparent power:	4,9 VA
Material:	aluminium	Effective power:	3,7 W
Illuminant:	replaceable 18 x 0,1W LED-module	Inrush current:	6 A / 98 µs
Nominal voltage AC:	230V ±10% 50/60 Hz	Protection class:	I
Nominal voltage DC:	176 - 264 V	Input terminals:	2.5mm ² feed through wiring
Nominal current AC:	21 mA	Temperature ta:	-15...+40 °C
Nominal current DC:	17 mA		

Articles

SNP 7135 LED J/SV		
Colors	Aluminium	RAL (special)
Art. no.	101955181	104674821
wall mounting	Light colour: 6500 K	Protection category: IP40



Name	Accessories	Art. no.
J-ET 5.1 SV-max. 24V DC320mA const.	spare part	101422893
Legend panel 7x35 PL	required	101948212
Legend panel 7x35 PLO	required	101947707
Legend panel 7x35 PLU	required	101947909
Legend panel 7x35 PO	required	101948010
Legend panel 7x35 PR	required	101948111
Legend panel 7x35 PRO	required	101947606
Legend panel 7x35 PRU	required	101947808
Legend panel 7x35 PU	required	101948313
Legend panel 7x35 custom design		101871016
Spare part - LED unit SNP 7135	spare part	101969531

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

