



Single sided aluminium profile emergency exit luminaires with additional light output at bottom side. Homogeneous illumination by state-of-the-art LED technology with a luminance of > 500 cd/m².

Technical data

viewing distance:	60 m
Material:	aluminium
illuminant:	4 x 1W LED-module
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	27 mA
Nominal current DC:	28 mA

Apparent power:	6,3 VA
Effective power:	6,0 W
Inrush current:	6 A / 22 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C

Articles

SNP 7160 FLD 230V	
Colors	Aluminium
Art. no.	101397938
wall mounting	Light colour: 6500 K Protection category: IP40



Name	Accessories	Art. no.
FLD 230/4 - CC - 320 - L	spare part	101965083
Legend panel 7x60 PL	required	101950232
Legend panel 7x60 PO	required	101950030
Legend panel 7x60 PR	required	101950131
Legend panel 7x60 PU	required	101950333
Legend panel 7x60 custom design		101871218
Piktogrammscheibe 7x60hochkant Sonder n. Vorgabe	optional	104822846

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

