




Single sided aluminium profile emergency exit luminaires with additional light output at bottom side. Homogeneous illumination by state-of-the-art LED technology with a luminance of  $> 500 \text{ cd/m}^2$ .

### Technical data

<b>viewing distance:</b>	60 m	<b>Apparent power:</b>	8,3 VA
<b>Material:</b>	aluminium	<b>Effective power:</b>	7,4 W
<b>Illuminant:</b>	4 x 1W LED-module	<b>Inrush current:</b>	8 A / 50 $\mu\text{s}$
<b>Nominal voltage AC:</b>	230V $\pm 10\%$ 50/60 Hz	<b>Protection class:</b>	I
<b>Nominal voltage DC:</b>	176 - 264 V	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Nominal current AC:</b>	36 mA	<b>Temperature ta:</b>	-15...+40 °C
<b>Nominal current DC:</b>	32 mA		

### Articles

SNP 7160 LED J/SV		
Colors	-	Aluminium
Art. no.	105008863	101291137
wall mounting	Light colour: 6500 K	Protection category: IP40



Name	Accessories	Art. no.
J-ET 9/24 SVmax.24VDC,320mAconst	spare part	101420267
Legend panel 7x60 PL	required	101950232
Legend panel 7x60 PO	required	101950030
Legend panel 7x60 PR	required	101950131
Legend panel 7x60 PU	required	101950333
Legend panel 7x60 custom design		101871218
Piktogrammscheibe 7x60hochkant Sonder n. Vorgabe	optional	104822846

**Info:** When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

