

230V**SNP 7168.1 UP Aluminium luminaires**

For connection to FUSION central battery- or emergency power (NEA) systems



Single sided aluminium profile emergency exit luminaires for recessed wall mounting. Invisible frame with an installation depth of 60mm. Homogeneous illumination by state-of-the-art LED technology with a luminance of $> 500\text{cd/m}^2$.

Technical data


viewing distance:	32 m
Material:	aluminium
Illuminant:	2 x 1W LED-module
Nominal voltage AC:	230V $\pm 10\%$ 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	19 mA
Nominal current DC:	18 mA

Apparent power:	4,4 VA
Effective power:	4,0 W
Inrush current:	6 A / 22 μs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C

Articles

SNP 7168.1 UP FLD 230V	
Colors	Aluminium
Art. no.	101376114

recessed wall mounting Light colour: 6500 K Protection category: IP40



Name	Accessories	Art. no.
FLD 230/8 – CC – 320 – C	Ersatzteil	100903238
Legend panel SNP 7168 UP PL	required	101218587
Legend panel SNP 7168 UP PLO	required	101218789
Legend panel SNP 7168 UP PLU	required	101218991
Legend panel SNP 7168 UP PO	required	101219193
Legend panel SNP 7168 UP PR	required	101218688
Legend panel SNP 7168 UP PRO	required	101218890
Legend panel SNP 7168 UP PRU	required	101219092
Legend panel SNP 7168 UP PU	required	101218486
replacement kit SNP 7168.1 LEDUP	Ersatzteil	101944370

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

