



Single sided aluminium profile emergency exit luminaires with additional light output at bottom side. Homogeneous illumination by state-of-the-art LED technology with a luminance of $> 500 \text{ cd/m}^2$.

Technical data


Viewing distance:	60 m	Nominal current DC:	32 mA
Material:	Aluminium	Apparent power:	8,3 VA
Illuminant:	4 x 1W LED-module	Inrush current:	8 A / 50 μs
Nominal voltage AC:	230V $\pm 10\%$ 50/60 Hz	Protection class:	I
Nominal voltage DC:	176 - 264 V	Input terminals:	2.5mm ² feed through wiring
Nominal current AC:	36 mA	Temperature ta:	-15...+40 °C

Available colours Add colour code to the article no. e.g. 800 014 **LXX**

Special colour: **L99**

Articles

SNP 7183 LED J/SV	Art. no. 807 327
Wall mounting	Light colour: 6500 K Protection category: IP40



Name	Accessories	Art. no.
Legend panel 7x83 PRO	required	714 356
Legend panel 7x83 PLO	required	714 355
Legend panel 7x83 PRU	required	714 354
Legend panel 7x83 PLU	required	714 353
Legend panel 7x83 PU	required	714 055
Legend panel 7x83 PR	required	714 054
Legend panel 7x83 PL	required	714 053

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

