



Single sided aluminium profile emergency exit luminaires with additional light output at bottom side. Homogeneous illumination by state-of-the-art LED technology with a luminance of > 500 cd/m².

Technical data

Viewing distance:	12 m
Material:	Aluminium
Illuminant:	1 x 1W LED-module
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	16 mA
Nominal current DC:	14 mA


Apparent power:	3,6 VA
Effective power:	3,1 W
Inrush current:	6 A / 22 μs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C

Available colours Add colour code to the article no. e.g. 800 014 LXX

Special colour: L99

Articles

SNP 7184 FLD 230V	Art. no. 811 012
Wall mounting	Light colour: 6500 K Protection category: IP40



Name	Accessories	Art. no.
Legend panel 7x84 PLO without logo	required	714 341
Legend panel 7x84 PRO without logo	required	714 340
Legend panel 7x84 PLU without logo	required	714 339
Legend panel 7x84 PRU without logo	required	714 338
Legend panel 7x84 PU without logo	required	714 059
Legend panel 7x84 PR without logo	required	714 058
Legend panel 7x84 PL without logo	required	714 057

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

